

UN 1263**PRECAUTION****Contiene: Vapor de Petróleo****Inflamable. Asegurase en lugar ventilado. Aplicable para exterior solamente.**

Vapor peligroso. Talvez afecte el cerebro o el sistema nervioso causando mareos, dolores de cabeza. Causa sus ojos, piel, nariz, y garganta irritada. Si lo usa mal o al propósito to hule este producto puede pergunicarlo o fatal.

Solamente usuelo en lugar bien ventilado y adecuada. Si siente dolores de cabeza, mareos y ojos irritados, deje la área y pongas protección respiratoria (NIOSH/MSHA TC 23C o algo igual). Sierre el vote después de usaria. Lavese las manos después de agarrar oste producto.**ESTE PRODUCTO PUESE ENSEDERSE INSTANTNIAMENTE.** Ropa mojada de aceite, brochas, trapos, etc. Pongamos en agua y sierre completamente el vote manténgalo fuera de otros productos inflamables.**AVISO este producto contiene chemicals, conocidos de causar el cáncer y defectos de nacimiento y otras coaas mal.****Primera atención medica:** si a sido in gestionado, no intrudusa vomito. Llame a un doctor inmediatamente. Si se siente con dificultad respiratoria, deja el lugar y oblenga aire fresco. Si continúe con la misma experiencia, obtenga atención medica inmediatamente. Si tiene contacto con sus ojos, lavelos con mucha agua por los menos por 15 minutos y obtenga attention medica; en su piel lavese completamente con agua y jabón.**MANTENGALO FUERA DEL ALCANCE DE LOS NINOS****TRANSPARENT
NATURAL TONE****FOR HARDWOOD****PENOFIN®
PENETRATING OIL FINISH****99% U.V. PROTECTION
BRAZILIAN ROSEWOOD OIL****FOR:
EXOTIC HARDWOOD -
MAHOGANY - IPE - TEAK****ONE
COAT
FORMULA
EXTERIOR****NET 128 fl. oz.
(ONE GALLON)
3.785 liters****HARDWOOD MAINTENANCE**

Our use of Brazilian Rosewood oil as an important ingredient of PENOFIN® creates a stain that penetrates deeper and makes your wood last longer. Due to the density of exotic hardwoods such as Mahogany, Ipe, Teak, etc., more frequent maintenance coats are necessary at first. Penofin Hardwood Formula offers the best UV protection with 99% rating on dense hardwoods. Penofin complies with all national and local air quality regulations. V.O.C. Less than 250 grams per liter.

In addition to having high density, these unique hardwoods extract their natural moisture over longer periods of time. A maintenance coat of Penofin should be applied within 3-6 months after the initial application. The next maintenance coat should be done again in approximately 10-12 months. Over time the wood fibers will become fully protected and the maintenance will become less frequent. In well-traveled areas, keep the surface clean by sweeping and by washing occasionally with a mild detergent.

DIRECTIONS FOR USE: SHAKE WELL AND STIR THOROUGHLY. DO NOT THIN OR BLEND WITH OTHER PRODUCTS. DO NOT APPLY WHEN THE WOOD IS HOT TO THE TOUCH.

Penofin cannot be applied over other wood finishes. Be sure to completely strip or sand the entire surface if other paints or stains have been used. Clean wood surface before application. Surface must be free of dirt and sawdust buildup. Allow 48 hours drying time before applying the product.

APPLICATION: A brush or sprayer may be used. Brush thoroughly and back brush Penofin into the wood leaving no excess. Wipe entire surface after 20-30 minutes. Do not allow film to develop on wood surface. Application should be made with no chance of rain during the process or during the twelve-hour drying time. If rain occurs, spots may develop on wood surface. Do not apply in direct hot sun! Avoid contact with metal, i.e. metal brushes and steel wool.

Penetration of Penofin may not be uniform in all areas due to density and grain of wood. Product should be applied more often to horizontal areas that readily absorb Penofin and also areas with high ultraviolet exposure or heavy traffic.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to www.epa.gov/lead.**COVERAGE:** 200-300 square feet per gallon on smooth surface.**CLEAN UP:** Paint thinner or mineral spirits.**CAUTION Contains: Petroleum Distillate****Keep away from flame. Do not smoke during application. Assure cross ventilation. Avoid vapor build-up. For exterior application only.**

Vapor harmful. May affect the brain or nervous system causing dizziness, headache, or nausea. Causes eye, skin, nose, and throat irritation. Intentional misuse by deliberately concentrating or inhaling the contents may be harmful or fatal.

Use only with adequate ventilation. Avoid breathing vapors or spray mist during application and drying. If you experience eye watering, headaches, or dizziness, leave the area or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent). Close container after each use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.**DANGER:** Rags, steel wool or waste soaked with Penofin Exterior Wood Finish may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container away from building and other combustible materials. Dispose of in accordance with local regulations.**WARNING** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.**First aid:** If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty in breathing, leave area to obtain fresh air. If breathing difficulty continues, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.**KEEP OUT OF THE REACH OF CHILDREN****LIMITED WARRANTY:** Penofin exterior finishes are warranted to perform when applied to wood surfaces according to label instructions. If Penofin is shown to be defective, Performance Coatings Inc. will replace the product. Warranty is void if wood was previously finished or pretreated. Performance Coatings Inc.'s liability under any warranty whether expressed or implied is limited solely to replacement of product and does not include labor or other consequential damages.**MANUFACTURED BY PERFORMANCE COATINGS INC.
360 LAKE MENDOCINO DRIVE, P.O. BOX 1569 • UKIAH, CA 95482
1-800-PENOFIN • Se Habla Español • www.penofin.com***Penofin The World's Finest Wood Finish®***DANGER!**HARMFUL OR FATAL IF SWALLOWED.
VAPOR HARMFUL. COMBUSTIBLE LIQUID AND VAPOR.
See other Cautions on Back Panel.