



SIMPLE INGENUITY

LEVEL.IT ADJUSTABLE PEDESTALS

- Simple, extended height range pedestal
- Patented design features exclusive internal coupler
- Durable commercial quality
- Fast and easy installation promotes labor savings
- Screw-to-adjust pedestals ensure perfectly level decks
- Impervious to water, mold, and freeze/thaw cycles
- Long lasting solution with no maintenance over time
- Made in the U.S.A.



©2013-2020 United Construction Products, Inc. All Rights Reserved. Covered by one or more patents or pending patents.

Bison Innovative Products | 701 Osage Street, Unit 120, Denver CO 80204 USA | 800-333-4234 | www.bisonip.com

June 2020

SPECIFICATIONS

- Supports 750 lbs (340 kg) FoS:3 per pedestal
 Select 1/8 or 3/16 inch (3.2 or 4.5 mm) tab size for pedestals
 Level.It adjustable system height range is 2 to 12 inches (51 to 305 mm)
 Accessories available for heights from 1/8 to 2 inches (3.2 to 51 mm)
 Pedestals made of high density copolymer polypropylene
 Contains 20% post-industrial recycled material
 Impervious to water, mold, and freeze/thaw cycles
 Made in the U S A

- Made in the U.S.A.

		Model No.	Description	Height Range	Notes
Pedestals		LC-18 LC-316	Adjustable Pedestal	2" to 4-3/4" (51 to 121 mm)	
		C1	Coupler	Adds up to 1-1/2" (38 mm)	
		C4	Coupler	Adds up to 4″ (102 mm)	
Tabs		LT18 LT316	Spacer Tab		Select 1/8" (3.2 mm) or 3/16" (4.5 mm) Tab Width
Accessories	B	VT18 VT316	Ultra Low Height Pedestal	1/8" (3.2 mm)	
		HD25-18 HD25-316 HD50-18 HD50-316 HD75-18 HD75-316	Fixed Height Stackable Pedestal	1/4" (6 mm) 1/2" (13 mm) 3/4" (19 mm)	Stack up to 4 Supports 1250 lbs (567 kg) FoS:3 per Pedestal
		LO-18 LO-316	Low Height Adjustable Pedestal	1-1/4" to 2" (32 to 51 mm)	
		B11	Flexible Shim	1/16" (1.5 mm)	
		PS1	Rigid Shim	1/8" (3.2 mm)	
		LD4	Base Leveler	Adds 1/4" (6 mm)	Stack up to 4 total to base of Pedestals For 1/4" per foot (2%) slope compensation each
	ø.	FS-1	Wood Tile Fastening Kit		able Pedestals with long screw, ight Pedestals with short screw
	à	FS-12 FS-12-WT	12" Fastening Spline 3/16" (4.5 mm) Tab	Fastens Wood Tiles or Paver Trays to Adjustable Pedestals with long screw, and HD50 or HD75 Fixed Height Pedestals with short screw	
		JT	Joist Top Attachment	Adds 3/16" (4.5 mm)	Works with 2 x and 4 x lumber on Adjustable Pedestals
		FIB	Floating Insulation Base	12" x 12" x 11/16" (305 x 305 x 17 mm) For use over roofing systems with 20 to 40 psi insulation	
		FFB	Floating Foundation Base	12" x 12" x 1/4" (305 x 305 x 6 mm) For use over soil	
Mode	74" 374" el HD25 Model HD75			4.3/4" - 6 1/4" Model LC + C1 Gray Coupler	Base Leveler Model LD4 Stack up to 4
IMPORTANT: Refer to Level.It product specifications to ensure proper use and installation. Find specifications at www.bisonip.com. + C4 black Coupler 8 3/4 - 12 Model LC + 2x C4 Black Couplers Bison Innovative Products 701 Osage Street Unit 120 Denver CO 80204 USA 800-333-4234 www.bisonip.com - 2 Model LC + 2x C4 Black Couplers					

Bison Innovative Products | 701 Osage Street, Unit 120, Denver CO 80204 USA | 800-333-4234 | www.bisonip.com