FRAMING

Don't trust your framing to nails or deck screws - use codecompliant CAMO* Framing Screws for better holding power and stronger connections. These screws are specifically designed and load-rated for interior and exterior framing applications.



PROTECH™ **ULTRA 4** COATING INDUSTRY LEADING COATING SYSTEM

Our proprietary PROTECH Ultra 4 four-layer coating system protects your connections against the harshest environmental elements. Each layer works together to provide optimum corrosion resistance, UV and environmental protection, and torque reduction for a high-performing, long-lasting screw. Tested in accordance with ASTM G198, the coating meets or exceeds the protection of codeapproved hot-dip galvanized (ASTM A153, Class D) in ground contact general use pressure treated lumber (AWPA UC1-UC4A).



Our coating is tested 2X longer than industry standard
IGHEST so you can be confident your connections will last.

DESIGN DETAIL



COLOR AND COATING



LEARN MORE ABOUT OUR STRUCTURAL SCREWS.







COMMON APPLICATIONS:







DECK BLOCKING



INTERIOR GENERAL CONSTRUCTION PROJECTS



EXTERIOR GENERAL CONSTRUCTION PROJECTS

FRAMING SCREWS ARE AVAILABLE IN:





DRJ TER 2102-01 STRUCTURAL WOOD SCREW PROPERTIES

CAMO® Structural Screws are third-party tested, codecompliant, and certified by DrJ.

Our industry-leading coating protects your connections against the harshest environmental elements. And we've got your back - our products are guaranteed by a Lifetime Limited Warranty. Trust CAMO* when your connections count. Read the full warranty at camofasteners.com



AVAILABLE IN 50CT, 150CT, AND 1,000CT.



WE HELP CONTRACTORS, BUILDERS, AND WEEKEND WARRIORS BUILD BETTER.

We know how important it is to get jobs done fast and well, without sacrificing quality. It's why construction innovation is such a big part of what we do. To arm you with the right fasteners and tools for the job, every product is designed to kick your frustrations to the curb. Your needs are, and have always been our priorities for more than 60 years.



