

## Right Panel

### Penofin RenewAll

**Penofin RenewAll** brings old, worn wood and concrete to life. The thick elastomeric formula will fill cracks up to ¼" and correct unsightly splinters creating an attractive non-slip, non-skid and dirt resistant surface. Penofin RenewAll is for horizontal surfaces and will add years to the life of any deck, patio or porch.

**Coverage:** Approximately 75 sq.ft. per gallon. Requires 2-coats. Square feet can be calculated by multiplying length times width; i.e., 10' W X 25' L = 250 sq. ft.

**Surface Preparation:** For a flawless application, Penofin RenewAll must be able to adhere. Remove any loose splinters and replace rotting or severely damaged boards. Prepare stained, or weathered surfaces with Penofin Pro-Tech Cleaner. If the surface is severely weathered, sand to completely remove all loose wood fibers. Fill cracks larger than ¼" with exterior wood filler. New concrete or masonry surfaces should cure for 30 days before application, then treat with Penofin Pro-Tech Brightener.

Penofin RenewAll is not recommended for driveways or garage floors. Mildew stains and other organic stains should be cleaned with Penofin Pro-Tech Cleaner. Mildew stains are not caused by the coating or coating failure. Penofin – Renew All contains mildew inhibiting agents that protect the coating's film from mildew growth.

**Application:** Shake and stir thoroughly before and during use. If your project requires more than 1, container, blend all containers together to ensure uniformity of color. Use a nylon or polyester brush to apply Penofin RenewAll into cracks and rough areas before rolling. Use a 3/8" nap roller to apply a thick, even coat, lengthwise along the boards. Penofin RenewAll will dry in 4-6 hours, then apply a second coat. For best results on vertical surfaces, use Penofin 100% Acrylic Solid Stain which is available in complimentary colors.

Do not apply in direct sunlight, to hot surfaces or if the temperature is below 50 degrees Fahrenheit or may fall below 50 within 48 hours of application. Do not apply over wet or damp surfaces or when rain is imminent. Do not intermix with any other products or thin. Protect containers from freezing. For exterior use only.

**Cleanup and Disposal:** Clean brushes and equipment with soap and water. Dispose of empty cans or unused portion in accordance with local, state and federal regulations.

**Cautions:** **CAUTION! KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. Use only with adequate ventilation. Avoid breathing vapors, spray mist or sanding dust. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each

use. DO NOT TAKE INTERNALLY. WARNING: This product contains a chemical known to the State of California to cause cancer.

**WARNING!** If you scrape, sand or remove old paint from any surface you may release lead dust. LEAD IS TOXIC, EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH- approved respirator to control lead exposure. Clean up carefully with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting USEPA/Lead information Hotline at 1-800-424-5323 or visit [www.epa.gov/lead](http://www.epa.gov/lead).

**First Aid: Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention\* **If inhaled:** if affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention\* **If swallowed :** Drink 2 glasses of water. Get medical attention immediately. \*

- Call poison control center, hospital emergency room or physician immediately.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:**

**1 800 222 1222**