




# EVERCLIP<sup>®</sup>

HIDDEN FASTENER



## Installation Instructions

1/4" min. groove depth



### Grooved Board Requirements

1/8" min. groove height


1/4" min. bottom lip height

#### CALIFORNIA PROPOSITION 65 WARNING

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

For warranty information visit [EnvisionDecking.com](http://EnvisionDecking.com)

©2020 Envision Building Products LLC is a registered trademark and EverClip is a trademark of Envision Building Products LLC



## EverClip™ Hidden Deck Fastener Installation Instructions

The EverClip™ Hidden Deck Fastener is the fast, easy and secure way to install Evergrain® and Evergrain® Envision® grooved boards for a beautiful, barefoot-friendly surface. Please reference the Grooved Deck Board Requirements at right to ensure proper fastening prior to installation.

### Installing the Starter Board

1. To begin installation of your deck, face-fasten one edge of the starter board with Evergrain or Evergrain Envision deck screws. Use one screw at each joist along the “unclipped” edge of the board. This will likely be necessary on the outside edge of the deck and also along the edge abutting the structure.
2. Place the first EverClip hidden fastener firmly in the groove over the center of the joist (A) and partially drive the screw until the head is just above the deckboard surface (B). Do not fully drive the screw.
3. Repeat Step 2 down the length of the deck board at each joist. At butt joints there is an additional joist. Fasten with EverClip hidden fasteners over each joist.



### Installing the Next Deck Board

4. Slide the next deck board into place positioning it so that clips are fully inserted into the groove (C) along the entire length of the board.
5. Firmly fasten clips from Step 2 into place by fully driving each screw (D). The starter board and one side of the second board are now secured. Clips will provide uniform automatic ¼" spacing.
6. Repeat Steps 2 and 3 on the open edge of the second deck board.
7. Repeat Steps 4-6 until all deck boards are in place.



### Installing the Last Deck Board

8. Secure the open edge of the last deck board by fastening with Evergrain or Evergrain Envision deck screws.